



DATASHEET

EXA800-54X

The Exaware's EXA800-54X is based on Broadcom's StrataDNX® Qumran MXTM switch silicon capable of line-rate 800 Gbps Layer 2 and Layer 3 switching. The switch can be deployed either as a top-of-rack switch in the data center, or as a carrier access/aggregation switch.

The EXA800-54X hardware comes with high-availability design features, including redundant, hot-swappable AC or 48VDC PSUs, and 5+1 redundant fan modules with front-to-back airflow. The Exaware's EXA800-54X switch meets the high-performance, availability, and scalability requirements of cloud data centers and communication service providers.


KEY FEATURES AND BENEFITS

- High performance, data center top-of-rack and carrier access/aggregation switch.
- 48 x SFP+ switch ports, supporting 10 GbE (DAC, AOC, 10GBASE-SR/LR) or 1 GbE (1000BASE-T/SX/LX).
- 6 x 100G QSFP28 ports on the front.
- Support for IEEE1588v2 and SyncE functions in hardware.
- Rack mountable in standard 19" racks.
- Hot-swappable, load sharing, redundant AC or 48 VDC PSU power input options.
- Hot swappable 5+1 redundant fan modules.
- Management: Ethernet and console RJ-45 ports.
- Hardware switch pre-loaded with Open Network Install Environment (ONIE) for automated loading of compatible open source and commercial NOS offerings.
- Compatible with Open Network Linux (ONL).

SOFTWARE



INTERFACES



Description

| | |
|--------------------------|---------------------------------------|
| 1. 48 x SFP+ ports | 5. USB storage port |
| 2. 6 x QSFP28 port | 6. DC or AC PSU |
| 3. RJ-45 management port | 7. Grounding screw |
| 4. RJ-45 console port | 8. Hot-swappable 5 + 1 redundant fans |

PORTS

- Switch Ports:
 - 48 x SFP+ each supporting 10 GbE or 1 GbE
 - 6 x 100G QSFP28 each supporting 1 x 40/100 GbE
- Management Ports on Front Panel:
 - 1 x RJ-45 serial console
 - 1 x RJ-45 100/1000BASE-T management port
 - 1 x USB (storage)
 - 1 x BMC

KEY COMPONENTS

- Broadcom BCM88370 Qumran-MX
- CPU module:
 - Processor: Intel® Xeon® D-1518 processor 4-core 2.2 GHz
 - Memory: DDR4 SO-DIMM 8 GB x 2

PERFORMANCE

- Switching Capacity: 800 Gbps
- Processing Rate: 700 Mpps

SUPPORTED OPTICS AND CABLES

- SFP+ Ports:
 - 10GBASE-CR DAC: Up to 3 m passive; up to 10 m active
 - 10GBASE-SR: Up to 100/300 m over OM3 MMF
 - 10GBASE-LR: Up to 10 km over SMF
 - 10GBASE-ER4: Up to 40 km over SMF
 - 10GBASE-ZR: Up to 80 km over SMF
 - 1000BASE-SX, 1000BASE-LX, 100/1000BASE-T
- QSFP28 Ports:
 - 40GBASE-CR4 DAC: Up to 3 m passive; up to 10 m active
 - 40GBASE-CR4 DAC: Up to 4 x SFP+ 10GBASE-CR DAC; up to 3 m passive; up to 10 m active
 - 40GBASE-SR4: Up to 100 m over OM3 MMF, 150 m over OM4 MMF
 - 40GBASE-LR4: Up to 10 km over SMF
 - 100GBASE-SR4: 100 Gbps short-reach transceiver
 - 100GBASE-LR4: 100 Gbps long-reach transceiver
 - QSFP28 AOC Cable: 100 Gbps to 100 Gbps AOC cable with up to
 - 30 m 100G QSFP28 to 100G QSFP28

PHYSICAL AND ENVIRONMENTAL

- Dimensions (WxDxH): 438.4 x 501.9 x 44 mm (17.26 x 19.76 x 1.73 in)
- Weight: 9.7 kg (21.38 lb), with two installed PSU modules
- Fans: Hot-swappable 5+1 redundant fans
- Operating Temperature: 0°C to 40°C (32°F to 104°F)
- Storage Temperature: -40°C to 70°C (-40°F to 158°F)
- Operating Humidity: 5% to 95% non-condensing

POWER

- PSUs: 2 redundant, load-sharing, hot-swappable AC or 48 VDC
- AC Input Range: 100 – 240 VAC
- DC Input Range: -36 – -72 VDC

REGULATORY COMPLIANCE

- Safety Compatibility
 - CB
 - UL/CUL
- EMI
 - CE Mark
 - EN55032 Class A
 - EN55024
 - EN61000-3-2
 - EN61000-3-3
 - FCC Part 15 Subpart B Class A VCCI Class A
- Environmental: NEBS Level 3
- RoHS 2.0 Compliant
- WEEE Standards: The switches complied with the following
 - WEEE standards: Waste Electrical and Electronic Equipment (WEEE Directive 2002/96/EC)

ROUTING PROTOCOLS

- IPv4, IPv6 Dual stack
- eBGP, iBGP at scale
- MP-BGP
- Multi-AS VPN/BGP-LU
- BGP signaling for L3VPN
- BGP signaling for L2VPN
- Seamless MPLS
- L3VPN
- L2VPN
- Inter-AS L3VPN
- 6PE and 6VPE
- VPWS
- H-VPLS
- OSPFv2, v3
- IS-IS – IPv4/IPv6, Multi topology
- Route distribution across protocols
- PIM-SSM/SM
- IGMPv3
- LDP, T-LDP
- RSVP-TE
- IGP shortcut
- OSPF-TE
- ISIS-TE
- Internet Access
- NH Tracking
- VRRP V2, V3 IPv4/IPv6
- Static-Route
- BGP RPKI
- Route leak
- DHCP Snooping

TIMING

- SyncE
- IEEE1588

MANAGEMENT

- Hierarchical, Commit based CLI
- NETCONF
- SSH
- Telnet
- Out-of-band and in-band management
- SNMPv2/V3
- RBAC
- AAA/TACACS+/Radius
- NTP
- Syslog
- Rich, Hierarchical Policy
- Language
- Enhanced logging
- Optical monitoring

SECURITY

- Data Path ACL
- Control Plane ACL
- Management VRF Separation
- Hardware policing for CPU traffic
- MD5 for routing protocols
- BGP FlowSpec

HIGH AVAILABILITY

- Process restart
- Graceful restart for all routing protocols

QOS & POLICY

- Hierarchical Shaping
- Per PORT/VLAN rate control
- WRED
- Weighted and strict priority queues
- Minimum latency queues
- 8 Queues per port/VLAN
- Ingress policing
- PRI/DSCP/EXP classification
- Flexible packet fields classification
- Ethernet EBN (MW dynamic rate)

DATA PATH

- VLAN
- QinQ for all services
- LAG
- MPLS FRR
- IP-LFA
- Hierarchical FIB
- BGP-PIC Core/Edge
- Two level load-balancing
- VRF at scale
- BFD

INFRASTRUCTURE

- ONIE Bootloader
- Standard ONL
- Embedded KVM Hypervisor

Ordering Part Number:

Description:

| | |
|---------------------|---|
| EXA800-54X-A-AC | Router System with Software and AC Power Supplies |
| EXA800-54X-A-DC | Router System with Software and DC Power Supplies |
| EXA800-54X-A-NOS | Router System Software |
| EXA800-54X-A-FAN | Spare Fan |
| EXA800-54X-A-PSU-AC | Spare AC Power Supply |
| EXA800-54X-A-PSU-DC | Spare DC Power Supply |

[Get a Quote >](#)